



1800MHz+N78 A033 5G Signal Repeater



OVERVIEW

ATNJ RF repeater with industrial design, combines multi mobile network signals together and improves the mobile voice and data communication, aiming to provide a more cost-effective solution for signal. ATNJ RF repeater is easy to install and maintain, which could help signal providers get fast solution.

A repeater is working as a relay between the BTS and mobiles. It picks up the strongest signal from BTS via the Donor Antenna, linearly amplifies the signal and then re-transmits it via the Indoor Signal Distribution System to the weak/blind coverage area. And the mobile signal is also amplified and re-transmitted to the BTS via the opposite direction.

FEATURES

- Improve any two mobile networks at the same time
- LCD display the input/output signal strength
- Auto isolation detect function
- Auto gain control
- Auto level control
- Auto uplink noise reduction, avoid disturbing to BTS
- Smart LCD to guide the installation
- Golden color metal industrial design

WHERE TO USE

- Indoor: Hotels, Exhibition Centers, Basement, Parking Lots, Shopping Malls, Apartments..
- Outdoor: Airport, Tunnel, Village, Mining Area, Court, Tourism Area..

APPLICATION SCENE



Technical Specification

SPECIFICATIONS		PARAMETERS	
Frequency Range		1800MHz	1710-1785/1805-1880MHz
		3300-3800MHz	Customizable
Band Width		1800MHz	75MHz
		3300-3800MHz	Customizable
Gain		$68 \pm 3\text{dB}$	
Automatic Gain Control		31dB	
MGC (Step Attenuation)		20dB@ 1dB/Step	
Output Power		$17 \pm 3\text{dBm}$	
Spurious Emission	9 kHz -150 kHz/1kHz	$\leq -36\text{dBm}$	
	150 kHz - 30 MHz/10kHz	$\leq -36\text{dBm}$	
	30 MHz - 1 GHz/100kHz	$\leq -36\text{dBm}$	
	1 GHz- 12.75 GHz/1MHz	$\leq -30\text{dBm}$	
ACPR		Uplink Fully comply with 3GPP 36.106	
		Downlink Fully comply with 3GPP 36.106	
Unwanted emissions		Fully comply with 3GPP 36.106	
VSWR		≤ 2	
Ripple	GSM 900MHz	$\leq 6\text{dB}$	
	DCS 1800MHz	$\leq 6\text{dB}$	
	UMTS 2100MHz	$\leq 6\text{dB}$	
Noise Figure		$\leq 5\text{dB}$	
Delay		$\leq 1 \mu\text{s}$	
I/O Impedance		50Q	
RF Connector(Customers to		SMA-Type (Female)	

Choose)	
Operating Temperature	-25°~+55°
Power Supply	DC 5V
Power consumption	≤75W
Environment Conditions	IP43
Humidity	≤90%
Weight	0.5kg
Size	205*165*45mm